

# inverELITE<sup>V3</sup>

## SUPERIOR EFFICIENCY. ADVANCED ENGINEERING. DESIGN APPEAL.

Powered by Madimack's InverMAC technology and engineered to include the latest user-features, InverELITE is a world-class pool heating solution. Unrivalled energy efficiencies, the quietest operation noise levels and market leading design makes it the ultimate heating partner for avid pool owners. Madimack's InverELITE series comes with Wi-Fi as a standard inclusion and operates at optimal levels even in coldest of conditions. The InverELITE series simply sets the standard for all other heaters.



### Backward Airflow System

Innovative backward airflow design draws air from both sides and blows it out from the back



### Premium Weatherproof Casing

The elegant casing gives a sleek, premium feel resistant to weather, UV and corrosion



### Soft Start

InverELITE will start from 0 amps and increase steadily protecting electrical systems



### Operation down to -15°C

Built to operate in the coldest weather and extend your pool season into the winter



### Built-in Wi-Fi

Built-in Wi-Fi and smart app provides convenience to control your pump on-the-go



### Smart & quick defrosting

InverELITE is equipped with reverse cycle defrosting detecting frost accumulation during operation and automatically switch to defrosting mode



madimack

Powered by  **invermac**  
TECHNOLOGY



## TECHNICAL PARAMETERS

Model	ESV3-110	ESV3-140	ESV3-170	ESV3-220	ESV3-270	ESV3-320	ESV3-400
<b>PERFORMANCE CONDITION: Air 27°C/ Water 27°C/ Humid. 80%</b>							
Heating capacity (kW)	11.5	14	17	22.5	26.9	31.8	40.5
COP Range	16.0 ~ 7.3	16.0 ~ 7.4	16.1 ~ 7.1	16.2 ~ 7.1	16.1 ~ 7.3	16.4 ~ 7.2	16.0 ~ 7.0
<b>PERFORMANCE CONDITION: Air 15°C/ Water 26°C/ Humid. 70%</b>							
Heating capacity (kW)	7.7	9.3	11.5	15.0	18.0	21.8	29.0
COP Range	7.5 ~ 5.0	7.6 ~ 5.1	7.8 ~ 5.0	8.2 ~ 5.1	7.9 ~ 5.1	8.0 ~ 5.2	8.3 ~ 5.1
<b>PERFORMANCE CONDITION: Air 35°C/ Water 26°C/ Humid. 70%</b>							
Cooling Capacity (kW)	4.6	5.6	6.5	8.1	10.2	12.2	15.0
<b>TECHNICAL SPECIFICATIONS</b>							
Operating air temperature (°C)	-15 ~ 43						
Compressor	Twin-Rotary Mitsubishi DC Compressor						
Heat exchanger	Twisted Titanium Heat Exchanger						
Casing	Marine Grade Aluminium Alloy						
Power supply	230V 1Ph						400V 3Ph
Electrical connection	10A plug	15A plug	Hard wired	Hard wired	Hard wired	Hard wired	Hard wired
Rated input power (kW)	0.24 ~ 1.79	0.29 ~ 2.16	0.36 ~ 2.67	0.45 ~ 3.33	0.54 ~ 4.0	0.59 ~ 4.36	0.78 ~ 5.8
Rated input current (A)	1.04 ~ 7.78	1.09 ~ 8.34	1.57 ~ 11.63	1.96 ~ 14.48	2.35 ~ 17.39	2.56 ~ 18.96	1.13 ~ 8.41
Maximum input current (A)	9	11	13	16	18	21	10.5
Sound level at 1m dB(A)	36.3 ~ 44.5	36.5 ~ 45.9	39.3 ~ 46.7	39.5~49.8	39.8~50.2	40.3 ~ 50.8	40.6 ~ 51.3
Sound level at 10m dB(A)	16.3~24.5	16.5 ~ 25.9	19.3 ~ 26.7	19.5~29.8	19.8~30.2	20.3 ~ 30.8	20.6 ~ 31.3
Advised water flow (L/Min) ±20	65	80	100	125	150	180	230
Water connection (mm)	40						
Net weight (kg)	66	73	75	91	114	136	160
Net dimension LxWxH (mm)	750x504x656	750x504x656	839x504x656	979x504x756	1132x514x756	1029x512x1107	1139x512x1106

\* The data above is only for reference. For specific data, please refer to the nameplate on the unit.  
 \* Acoustic data is to TuV international testing conditions, site conditions may differ